

Analog Telephone Adapter (CRA 210)

3 Ethernet Ports + 2 Phone Port + 1 Regular Line Port



Most advanced SIP-based telephone adapter on the market!

Our ATA has all the requirements to meet the needs of small or medium sized enterprise & home users, and consistently delivering clear voice quality. Designed and tested for full interoperability with leading IP-PBXs, Soft switches and most SIP-based environments

Key Features

- Connects legacy telephones (PSTN) to IP-based (VoIP) networks
- Caller ID, Call Waiting/Transfer/Hold and 3-way conference
- VAD, CNG, Echo Cancellation (G.168), Gain Adjustment & more
- Advanced adaptive jitter control and packet loss concealment
- Fax pass through and T.38 with QoS, Auto provisioning & STUN
- Built-in Router, NAT,DHCP, PPPoE, IP Address Reservation, Port Forwarding & Advanced Routing
- Firmware upgrade with classified user management
- Configure using a Web browser

Technical Specification

Model:	CRA-210
Ports:	Three 10/100Mbps RJ-45 Network Port Two RJ-11 FXS Port for VoIP One RJ-11 FXO port for PSTN
LED's:	Power, Ethernet, Phone1, Phone2, Line
Voice Protocol:	Session Initiation Protocol (SIP v2)
Voice Codec's:	G.711 A-law, G.711 μ -law, G.729AB,G.726, G.723.1
Ringer Equivalence	3 REN per RJ-11 port
Ring Frequency	25Hz
FXS Port Impedance	Pre-set Progress Tones for Multiple Regions including 600 / 900 ohms
Ring Voltage	90 Vrms Configurable
Security:	Password-protected management

Physical & Environment

Operating Temperature	10°C to 40°C (50°F to 104°F)
Operating humidity	10% to 90%, Non-condensing
Storage temperature	0°C to 50°C (32°F to 122°F)
Storage humidity	5% to 95%, Non-condensing
Unit Weight	0.32 kg
Dimensions	149 mm (W) x 180 mm (L) x 45 mm (H)
Power Input	12V DC / 1.5 A
Warranty	One Year

Other Models



allo.com

For more information please contact
Canada: 1 877 339 2556 | India: +91 80 67080808 | Email: info@allo.com