

ELECTRONICS TEST AND DEVELOPMENT CENTRE

(STQC Directorate, Ministry of Communications & Information Technology) 100 ft Road, Peenya Industrial Estate, Bangalore-560 058 (Tel: 2839 5992, 2839 4647. Fax: 080 - 2839 1804) E-mail:mailetdc29@yahoo.com



Page 01 of 17

Report No.: TR/EMC/61795-2

TEST REPORT

1. Scop	e	WEIBER (ASI)	
1.	Service request number	61795	
2.	Requested by (Name & Address of the Organization)	M/s.CEM Solutions Pvt. Ltd. #176, Ground Floor, EPIP Indl. Area, White Field, Bangalore-5600066	
3.	Description of the equipment:		
	a) Nomenclature	4 PORT BRI PCI	
	b) Manufactured by	CEM Solutions Pvt. Ltd.	
	c) Model / type no.	ALLO-2/4 BRI-EC	
	d) Serial no.	CB001	
4.	Date of submission of test samples	12/07/2012	
5.	Condition of test samples on receipt	Good	
6.	Date of start of tests	12/07/2012	
7.	Date of completion of tests	12/07/2012	
8.	Applicable test specification	FCC Part 15: 2007 Class B	
9.	Test category	Performance Test	
10.	Environment condition	Temp: 25±5 °C RH: 40 to 75%	

2. Major equipments used

> SN	Nomenclature	Make	Model	Cal. Due
1.	EMI Receiver	R&S	ESCI7	08-12-2012
2.	EMI Receiver	R&S	ESCI	11-10-2012
3.	Bi-Log Antenna	Electro-metrics	EM-6917B-1	02-07-2013
4.	LISN	EMCO	3825	25-01-2013

This report refers only to the item tested and shall not be reproduced except in full. Refer to Information contained on the cover.

OVERNMENT OF IN ELECTRONICS TEST & DEVELOPMENT CENTRE BANGALORE - 560 058 MATION TECH S.T.C

Date of release 30/06/2010

FM/081-10



ELECTRONICS TEST AND DEVELOPMENT CENTRE

(STQC Directorate, Ministry of Communications & Information Technology) 100 ft Road, Peenya Industrial Estate, Bangalore-560 058 (Tel: 2839 5992, 2839 4647. Fax: 080 - 2839 1804) E-mail:mailetdc29@yahoo.com

Report No.: TR/EMC/61795-2

Page 02 of 17

Test Parameter	: 1) Conducted Emission measurement on power line		
	2) Radiated Emission measurement @ 3mts. distance		
Specification	: FCC Part 15: 2007, Class B		
Detector used	: Quasi Peak (QP) / Average (Avg)		

Detector Bandwidth

Frequency (MHz)	Detector Bandwidth (kHz)	
0.15 - 30	9	
30 - 1000	120	

Limits:

Class B							
Conducted Emission measurement on power line			Radiated Emission measurement @ 3mts. distance				
Freq (MHz)	QP (dBµV)	AVG (dBµV)	Freq (MHz)	QP (dBµV/m)			
0.15 - 0.5 0.5 - 5 5 - 30	66-56 56 60	56-46 46 50	30 - 88 88-216 216-960 960-1000	40 43.5 46 54			

EUT Configuration: The EUT is a 4 PORT BRI PCI tested by connecting it in the PCI slot of CPU.

Remark: (i)The details of Accessories used in testing listed in Annexure 'A'. (ii)The Images of EUT and Test Setup for Radiated Emission measurement is shown in Annexure 'B' and 'C' respectively. (iii)The graphs of Conducted Emission measurement on power line and Radiated Emission measurement are shown in Annexure 'D' and 'E' respectively.

GOVERNMENT

ELECTRONICS TEST & DEVELOPMENT CENTRE BANGALORE - 560 058

Summary of test results:

Conducted Emission measurement on power line Meets the Class B Limits of FCC Part 15 Few Significant emission are reported in page no. 03

Radiated Emission measurement @ 3mts. Distance Meets the Class B Limits of FCC Part 15 Few Significant emission are reported in page no. 04

Mr